

## Products List

TYPE	COUPLES	I <sub>max</sub> (A)	U <sub>max</sub> (V)	Q <sub>c</sub> max(w)	ΔT <sub>max</sub> (°C)	DIMENSIONS			R (Ω)		
				ΔT = 0	Q <sub>c</sub> =0	(mm)					
				Th=27°C		L	W	H			
TEC1-12703	127	3	15.4	26.7	70	40	40	4.9	3.42		
TEC1-12704		4		36.8	70	40	40	4.5	3.02		
TEC1-12705		5		46.5	70	40	40	4.2	2.51		
TEC1-12706		6		53.3	70	40	40	3.8	1.98		
TEC1-12707		7		62.2	70	40	40	3.6	1.71		
TEC1-12708		8		71.1	70	40	40	3.4	1.51		
TEC1-12709		9		80.1	69	40	40	3.4	1.36		
TEC1-12710		10		88.9	69	40	40	3.3	1.08		
TEC1-12708		127		8	15.4	71.1	70	50	50	5.1	1.51
TEC1-12710				10		88.9	70	50	50	4.5	1.12
TEC1-12712	12		106.7	70		50	50	4.2	0.91		
TEC1-12714	14		124.4	70		50	50	4.3	0.81		
TEC1-12715	15		133.3	70		50	50	3.6	0.75		
TEC1-12718	18		160.1	70		50	50	3.6	0.68		
TEC1-12720	20		177.8	69		50	50	3.4	0.59		
TEC1-12722	22		195.6	69		50	50	3.4	0.55		
TEC1-12726	26		232.5	68		50	50	3.3	0.48		
TEC1-12730	30		266.7	68		50	50	3.1	0.43		
TEC1-12710	127	10	15.4	88.9	70	62	62	6.1	1.05		
TEC1-12712		12		106.7	70	62	62	5.9	0.91		
TEC1-12714		14		124.4	70	62	62	5.9	0.81		
TEC1-12715		15		133.3	70	62	62	5.8	0.75		
TEC1-12718		18		160.1	70	62	62	5.6	0.68		
TEC1-12720		20		177.8	70	62	62	5.6	0.59		
TEC1-12722		22		195.6	70	62	62	5.3	0.55		
TEC1-12726		26		232.5	69	62	62	4.3	0.48		
TEC1-12730		30		266.7	69	62	62	3.9	0.43		

Notes:

- 1.The operating temperature can be: 125°C, 150°C, 200°C.
- 2.The length of lead wire could be fixed by clients, the common length is 150mm.
- 3.The sealing of TE modules: Unsealing, Silicon, Epoxy, the normal sealing is silicon gel.
4. We can also provide customized service for thermoelectric cooling modules.